



XR SERIES

XR

EXTREME RYOBI

“EXTREME” has now become a shape in a power tool design. EXTREME series – RYOBI’s flagship power tools enhance user’s skill by high performance and maneuverability. You will intuitively feel the quality. It offers you an excitement and a pride through using and owning the tool.

Specifications

Model	Voltage	Maximum Torque	Capacity	Rotation Speed	Blows Per Minutes	Charging Time	Battery Type	Overall Dimensions	Weight
BID-10XR	18 V	180 N·m	- Screw M4 ~ 8	- High 0 ~ 2,900 min ⁻¹	- High 0 ~ 4,10 min ⁻¹	47 minutes	Li-ion 6,000 mAh	106 x 79 x 240 mm	1.5 kg
			- Bolt M5 ~ 16 - High strength bolt M5 ~ 14	- Mid 0 ~ 2,100 min ⁻¹	- Mid 0 ~ 2,40 min ⁻¹				
BID-11XR	18 V	165 N·m	- Screw M4 ~ 8	- High 0 ~ 2,900 min ⁻¹	- High 0 ~ 4,40 min ⁻¹	47 minutes	Li-ion 1,500mAh x1, 6,000mAh	99.4 x 79 x 217 mm (1,500mAh) 99.4 x 79 x 237 mm (6,000mAh)	1.1 kg (1,500mAh) 1.4 kg (6,000mAh)
			- Bolt M5 ~ 14 - High strength bolt M5 ~ 12	- Mid 0 ~ 2,000 min ⁻¹	- Mid 0 ~ 3,30 min ⁻¹				
BG-11XR	18 V	10 mm	- High 0 ~ 8,000 min ⁻¹	- High 0 ~ 8,000 min ⁻¹	47 minutes	Li-ion 6,000 mAh	311 x 117 x 129 mm	1.9 kg	
			- Mid 0 ~ 6,000 min ⁻¹	- Mid 0 ~ 6,000 min ⁻¹					
BRJ-11XR	18 V	10 mm	- High 0 ~ 3,900 min ⁻¹	- High 0 ~ 3,900 min ⁻¹	47 minutes	Li-ion 6,000 mAh	349 x 79 x 123 mm	1.8 kg	
			- Mid 0 ~ 3,600 min ⁻¹	- Mid 0 ~ 3,600 min ⁻¹					
BNW-11XR	18 V	165 mm	- High 0 ~ 4,100 min ⁻¹	- High 0 ~ 4,100 min ⁻¹	4 minutes	Li-ion 6,000 mAh	287 x 201 x 258 mm	3.2 kg	
			- Mid 0 ~ 3,000 min ⁻¹	- Mid 0 ~ 3,000 min ⁻¹					

XR SERIES

BID-10XR



Voltage	18V
Maximum Torque	180 N·m
Capacity	- Screw M4 ~ 8 - Bolt M5 ~ 16 - High strength bolt M5 ~ 14
Rotation Speed	- High 0 ~ 2,900 min ⁻¹ - Mid 0 ~ 2,100 min ⁻¹ - Low 0 ~ 1,000 min ⁻¹ - Tek 0 ~ 2,900 min ⁻¹ - Lock on 0 ~ 2,500 min ⁻¹
Blows Per Minutes	- High 0 ~ 4,100 min ⁻¹ - Mid 0 ~ 2,400 min ⁻¹ - Low 0 ~ 1,200 min ⁻¹ - Tek 0 ~ 1,600 min ⁻¹
Charging Time	47 minutes
Battery Type	Li-ion 6,000 mAh
Overall Dimensions	106 x 79 x 240 mm
Weight	1.5 kg

- * 180 N·m high torque.
- * 106 mm short length.
- * 5-mode change for versatile operations.
- * IP56 rating Wet & Dust protection.
- * “No shadow” High brightness 3 LED lights.
- * Shock absorbing “Gel Sheet” for comfortable operation.

BID-11XR



Voltage	18V
Maximum Torque	165 N·m
Capacity	- Screw M4 ~ 8 - Bolt M5 ~ 14 - High strength bolt M5 ~ 12
Rotation Speed	- High 0 ~ 2,900 min ⁻¹ - Mid 0 ~ 2,000 min ⁻¹ - Low 0 ~ 900 min ⁻¹ - Tek 0 ~ 2,900 min ⁻¹ - Lock on 0 ~ 2,500 min ⁻¹
Blows Per Minutes	- High 0 ~ 4,400 min ⁻¹ - Mid 0 ~ 3,300 min ⁻¹ - Low 0 ~ 1,500 min ⁻¹ - Tek 0 ~ 1,800 min ⁻¹
Charging Time	24 minutes (1,500 mAh), 47 minutes (6,000 mAh)
Battery Type	Li-ion 1,500 mAh x1, 6,000 mAh x1
Overall Dimensions	99.4 x 79 x 217 mm (1,500 mAh) 99.4 x 79 x 237 mm (6,000 mAh)
Weight	1.1 kg (1,500 mAh) 1.4 kg (6,000 mAh)

- * 99.4 mm shortest length in its class.
- * High power and compact new BL motor.
- * 5-mode change for versatile operations.
- * IP56 rating wet & dust protection.
- * “No shadow” High brightness 3 LED lights.
- * Shock absorbing “Gel Sheet” for comfortable operation.

BG-11XR



Grinder wheel is not included.

Voltage	18V
Wheel size	100 mm
Rotation Speed	- High 0 ~ 8,000 min ⁻¹ - Mid 0 ~ 6,000 min ⁻¹ - Low 0 ~ 3,000 min ⁻¹
Switch type	Slide
Housing diameter	48 mm
Charging Time	47 minutes
Battery type	Li-ion 6,000 mAh
Overall Dimensions	311 x 117 x 129 mm
Weight	1.9 kg

- * High power new BL motor enables cutting concrete of 25mm in thickness.
- * Smallest grip diameter (48 mm) and shortest body (311 mm) in its class.
- * Compact round gear head ensures maximum cutting depth in any angle.
- * 3-mode rotation change for versatile operations.

BRJ-11XR



Voltage	18 V
Stroke Per Minutes	- High 0 ~ 3,900 min ⁻¹ - Mid 0 ~ 3,600 min ⁻¹ - Low 0 ~ 3,300 min ⁻¹
Length of stroke	10 mm
Charging Time	47 minutes
Battery Type	Li-ion, 6,000 mAh
Overall Dimensions	349 x 79 x 123 mm
Weight	1.8 kg

- * Adjustable 3 speed change depending on application and cutting material.
- * Uniquely designed compact and light weight reciprocating saw for one-hand operation.
- * IP56 rating Wet & Dust protection.
- * “No shadow” High brightness 3 LED lights.
- * For variety of applications including renovation, construction, plumbing, electric works and also for fruit harvesting.

BNW-11XR



Voltage	18 V
Blade Diameter	165 mm
Blade Bore	20 mm
Max Cutting Capacity	66 mm (90 degree)
Rotation Speed	4,100 min ⁻¹
Charging Time	47 minutes
Battery Type	Li-ion, 6,000 mAh
Overall Dimensions	287 x 201 x 258 mm
Weight	3.2 kg

- * New BL motor delivers high power (Max. output 800W).
- * Lightweight for comfortable and accurate operation.

Specifications

Model	Voltage	Stroke Per Minutes	Length of stroke	Charging Time	Battery Type	Overall Dimensions	Weight		
BRJ-11XR	18 V	- High 0 ~ 3,900 min ⁻¹	10 mm	47 minutes	Li-ion 6,000 mAh	349 x 79 x 123 mm	1.8 kg		
		- Mid 0 ~ 3,600 min ⁻¹							
		- Low 0 ~ 3,300 min ⁻¹							
Model	Voltage	Blade Diameter	Blade Bore	Max Cutting Capacity	Rotation Speed	Charging Time	Battery Type	Overall Dimensions	Weight
BNW-11XR	18 V	165 mm	20 mm	66 mm (90 degree)	4,100 min ⁻¹	47 minutes	Li-ion 6,000 mAh	287 x 201 x 258 mm	3.2 kg